PRODUCT SPECIFICATION SHEET

LM6 LED Spotlight



A larger-sized surface mount spotlight. Supplied with mounting bracket. Available in a range of finishes, this fitting can be rotated and tilted to point directly at any objects to be illuminated. This fitting is great for indoor display lighting and is suitable for use where access above or below the mounting surface is not available.

Of course, like for all models in this range there are also high CRI LED array options available making it very suitable for use in display lighting applications. The XIM & XTM module options make for a very high powered spotlight fitting.

GENERAL INFORMATION

Light Source	White Light LED
LED Module Options	Xicato XIM or Xicato XTM
Colour Temp. Options	2700K or 3000K
Operating Environment	IP20 rated for indoor use only
Material	Aluminium
Available Finishes	Black as standard. Custom RAL finish available to special order
Dimensions	79mm Diameter x 119mm Length
Securing Method	Surface mount, secured with screws

ARTICULATION

Rotation	360°
Tilt	120° lockable

XIM MODULE

Power Requirements	48V Constant Voltage
Module Options	9mm LED - 80CRI - 18.8W - 1300lm 9mm LED - 95CRI - 12.5W - 700lm
	19mm LED - 80CRI - 12.6W - 1300lm 19mm LED - 95CRI - 17.2W - 1300lm

XTM MODULE

Power Requirements	Constant Current
Module Options*	9mm LED - 80CRI - max. 15.6W - 1300lm 9mm LED - 95CRI - max. 23.6W - 1300lm
·	19mm LED - 80CRI - max. 19.9W - 2700lm 19mm LED - 95CRI - max. 19.9W - 2140lm

^{*}Lower power options are available if required - contact us for details

OPTICS DATA

Optics Options 9mm LED	12° / 20° / 23° / 35°
Optics Options 19mm LED	21° / 25° / 28° / 41° / 62°

DRIVER DIMMING OPTIONS

Xicato XIM Modules	Bluetooth
Xicato XTM Modules	DALI, 0-10V or mains

OPTICAL ACCESSORIES

Option 1	Honeycomb louver
Option 2	Diffuser lens
Option 3A	Straight 50mm snoot
Option 3B	Angled 50mm snoot

On models fitted with XIM modules only 1 optical accessory can be fitted at a time. Models fitted with XTM modules can accept 2 optical accessories at once.






MOUNTING ACCESSORIES

Side Cable Exit Adaptor Product Code: UFO-LM-SCEA

Allows the cable to exit from the side of the mounting foot rather than straight through the back face.



PRODUCT CODES

MODEL	OPTICS		COLOUR TEMP		FINISH		MODULE		ACCESSORIES	
LM6	9mm / 12°	12	2700K	27	Black	BL	XIM / 9mm LED - 80CRI	XI0980	None	XX
	9mm / 20°	20	3000K	30	Custom	CU	XIM / 9mm LED - 95CRI	XI0995	Honeycomb	НС
	9mm / 23°	23					XIM / 19mm LED - 80CRI	XI1980	Diffuser Lens	DF
	9mm / 35°	35					XIM / 19mm LED - 95CRI	XI1995	Straight Snoot	SS
	19mm / 21°	21					XTM / 9mm LED - 80CRI	XT0980	Angled Snoot	AS
	19mm / 25°	25					XTM / 9mm LED - 95CRI	XT0995		
	19mm / 28°	28					XTM / 19mm LED - 80CRI	XT1980		
	19mm / 41°	41					XTM / 19mm LED - 95CRI	XT1995		
	19mm / 62°	62								
LM6 -			-		-			-		







If you require 2 accessories, detail both codes in the accessories field.



Mobile +44 (0)779 358 1314